

HPD UNIQUE IDENTIFIER: 274506578944
CLASSIFICATION: 09 30 13 Ceramic Tiling
PRODUCT TYPE: Ceramic (Tile)
PRODUCT DESCRIPTION: Thanks to their excellent technical performance, Laminam slabs are ideal for the most delicate of uses, requiring maximum hygiene and resistance. The aesthetic virtues and the large size offer a major artistic advantage, guaranteeing material continuity throughout the settings, in sophisticated, natural shades.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY		
Inventory Reporting Format	Residuals/Impurities Evaluation	For all contents above the threshold, the manufacturer has:
→ Basic Method	→ Completed	
Threshold Disclosed Per	Explanation(s) provided :	
→ Product	Yes	Characterized Yes
Threshold Level		Screened Yes
→ 100 ppm		Identified Yes
		Provided name and CAS RN or other identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

PRODUCT | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE

LAMINAM PORCELAIN SLABS [SILICA, AMORPHOUS (PRIMARY CASRN IS 7631-86-9) BM-1 | CAN | MAM FELDSPAR LT-UNK | MAM MULLITE (AL6O5(SIO4)2) LT-UNK QUARTZ BM-1 * | CAN | MAM | GEN ZIRCONIUM SILICATE LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 0
Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... BM-1
Nanomaterial ... No
INVENTORY AND SCREENING NOTES:

Ceramic tile is considered one component resulting from the reactions inside the high temperature kiln-firing process (1225°C or 2237°F). The final product (ceramic porcelain slabs for kitchen countertops, tables, furnishing elements, floor and walls, for internal and external use) are inert and fully vitrified.

*Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. For this reason, this score is intentionally omitted from the "Contents highest concern" line above. See HPDC's Special Conditions policy for more information.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT
VOC Content data is not applicable for this product category.

COMPLIANCE See Section 3 for additional listings.
VOC emissions: Inherently non-emitting source per LEED

CONSISTENCY WITH OTHER PROGRAMS
No pre-checks completed or disclosed.

PFAS DETAILS:
This product does not contain intentionally added PFAS and materials and substances from suppliers are verified to not contain PFAS.

Attestation:
QHSE department
2026-01-19

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 3.0, available on the HPDC website at: www.hpd-collaborative.org/hpd-3-0-standard

LAMINAM PORCELAIN SLABS

PRODUCT THRESHOLD: 100 ppm RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

RESIDUALS AND IMPURITIES NOTES: Ceramic tile is considered as a single component resulting from the vitrification process in the high temperature kiln process. Since individual chemical components are not made available from the finished product, residuals and impurities have no separate impact in the preparation of this HPD.

OTHER PRODUCT NOTES: The finished product is odorless, non-flammable, do not release hazardous materials after installation.

SILICA, AMORPHOUS (PRIMARY CASRN IS 7631-86-9) ID: 107497-59-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-01-19 3:26:47		
%: 60.0000 - 80.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Ceramic body	
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS		
CAN	GHS - Japan		H350 - May cause cancer [Carcinogenicity - Category 1A]		
CAN	GHS - Australia		H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]		
MAM	GHS - Japan		H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]		
MAM	GHS - Japan		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
MAM	GHS - Australia		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION		
RESTRICTED LIST	Green Science Policy Institute (GSPI)		GSPI - Six Classes Precautionary List		
			Antimicrobials		

SUBSTANCE NOTES: A range is given due to the variable product thickness, various color options, and due to the variable composition of naturally occurring materials. Hazard components with occupational exposure limits are associated only to airborne particulates present into the dust produced by dry-cutting product during installation or by any other operations, including demolition/removal projects. When cutting, grinding or removing, use equipment with integral dust collection and/or use local exhaust ventilation. Use wet cutting methods to reduce generation of dust. Use respiratory protection.

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2026-01-19 3:38:35

%: 0.0000 - 20.0000

GreenScreen: LT-UNK

RC: None

NANO: No

SUBSTANCE ROLE: Ceramic body

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: A range is given due to the variable product thickness, various color options, and due to the variable composition of naturally occurring materials. Hazard components with occupational exposure limits are associated only to airborne particulates present into the dust produced by dry-cutting product during installation or by any other operations, including demolition/removal projects. When cutting, grinding or removing, use equipment with integral dust collection and/or use local exhaust ventilation. Use wet cutting methods to reduce generation of dust. Use respiratory protection.

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2026-01-19 3:39:49

%: 0.0000 - 20.0000

GreenScreen: LT-UNK

RC: None

NANO: No

SUBSTANCE ROLE: Ceramic body

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: A range is given due to the variable product thickness, various color options, and due to the variable composition of naturally occurring materials. Hazard components with occupational exposure limits are associated only to airborne particulates present into the dust produced by dry-cutting product during installation or by any other operations, including demolition/removal projects. When cutting, grinding or removing, use equipment with integral dust collection and/or use local exhaust ventilation. Use wet cutting methods to reduce generation of dust. Use respiratory protection

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-01-19 3:44:00	
%: 0.0000 - 20.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Ceramic body
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen**		
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route**		
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)**		
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man**		
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources**		
CAN	IARC	Group 1 - Agent is Carcinogenic to humans**		
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen**		
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]**		
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]**		
CAN	GHS - New Zealand	Carcinogenicity category 1**		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]**		
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]**		
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]**		
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1**		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		

SUBSTANCE NOTES: A range is given due to the variable product thickness, various color options, and due to the variable composition of naturally occurring materials. Hazard components with occupational exposure limits are associated only to airborne particulates present into the dust produced by dry-cutting product during installation or by any other operations, including demolition/removal projects. When cutting, grinding or removing, use equipment with integral dust collection and/or use local exhaust ventilation. Use wet cutting methods to reduce generation of dust. Use respiratory protection.

**Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information.

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2026-01-19 3:48:56

%: 0.0000 - 1.0000

GreenScreen: LT-UNK

RC: None

NANO: No

SUBSTANCE ROLE: Ceramic body

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: A range is given due to the variable product thickness, various color options, and due to the variable composition of naturally occurring materials. Hazard components with occupational exposure limits are associated only to airborne particulates present into the dust produced by dry-cutting product during installation or by any other operations, including demolition/removal projects. When cutting, grinding or removing, use equipment with integral dust collection and/or use local exhaust ventilation. Use wet cutting methods to reduce generation of dust. Use respiratory protection



Section 3: Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	Inherently non-emitting source per LEED	
COMPLIANCE TYPE: Self-declaration	ISSUE DATE: 2026-01-19	EXPIRY DATE: No expiration
CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: None		
COMPLIANCE DETAILS:		
COMPLIANCE SCOPE:		
APPLICABLE FACILITIES: All		
COMPLIANCE URL:		
COMPLIANCE NOTES:		



Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.



Section 5: General Notes

This HPD covers all Laminam products in general, including those with and without a fiberglass scrim. The formulation of all products are the same, with the variability coming from the thickness of the product, as well as the inclusion of the fiberglass scrim. Additionally, all color options are included, causing some formulation variability noted above.

MANUFACTURER INFORMATION

MANUFACTURER: **Laminam S.p.A.**
 ADDRESS: **Via Ghiarola, 258**
Fiorano Modenese, Emilia Romagna 41042
 COUNTRY: **Italy**

WEBSITE: **<https://www.laminam.com>**
 CONTACT NAME: **Quality Department**
 TITLE: **Quality Manager, Quality Specialists, and Quality Assistant**
 PHONE: **+39 0536 1844200**
 EMAIL: **quality@laminam.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold	Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold	Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold	Substances listed individually per threshold indicated per product

Nano	Composed of nano scale particles or nanotechnology
Third Party Verified	Verification by independent certifier approved by HPDC
Preparer	Third party preparer, if not self-prepared by manufacturer
Applicable facilities	Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.